

SAFETY DATA SHEET

1. Identification

maommoutom		
Product number	1000010102	
Product identifier	19 OZ SW PENETRATING COIL CLNR LB 12	2PK
Company information	Sprayway, Inc. 1000 INTEGRAM DR Pacific, MO 63069 United States	
Company phone	1-630-628-3000	
Emergency telephone US	1-866-836-8855	
Emergency telephone outside US	1-952-852-4646	
Version #	01	
Recommended use	cleaner	
Recommended restrictions	None known.	
2. Hazard(s) identification		
Physical hazards	Flammable aerosols	Category

Physical hazards	Flammable aerosols	Category 1	
Health hazards	Serious eye damage/eye irritation	Category 2	
	Sensitization, skin	Category 1	
OSHA defined hazards	Not classified.		
Label elements			



Signal word	Danger	
Hazard statement	Extremely flammable aerosol. May cause an a	allergic skin reaction. Causes serious eye irritation.
Precautionary statement		
Prevention	flame or other ignition source. Pressurized con	surfaces No smoking. Do not spray on an open ntainer: Do not pierce or burn, even after use. Avoid g. Contaminated work clothing must not be allowed e protection. Wear protective gloves.
Response	Remove contact lenses, if present and easy to	s: Rinse cautiously with water for several minutes. o do. Continue rinsing. If skin irritation or rash ritation persists: Get medical advice/attention. Wash
Storage	Protect from sunlight. Do not expose to tempe	eratures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance v	with local/regional/national/international regulations.
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 3
	Hazardous to the aquatic environment, long-term hazard	Category 3
Hazard(s) not otherwise classified (HNOC)	None known.	
Supplemental information	None.	

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	2.5 - 10

Chemical name	Common name and synonyms	CAS number	%
2-Butoxyethanol		111-76-2	1 - 2.5
Diethylene Glycol Monoethyl Ethe	r	111-90-0	1 - 2.5
EDTA Tetrasodium Salt		64-02-8	1 - 2.5
Propane		74-98-6	1 - 2.5
Lemon Terpenes		68917-33-9	0.1 - 1
Sodium Nitrite		7632-00-0	0.1 - 1
Terpene Hydrocarbons		68956-56-9	0.1 - 1
Other components below reportab	le levels		80 - 90

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Eye contact	If eye irritation persists: Get medical advice/attention.
Ingestion	In the unlikely event of swallowing contact a physician or poison control center.
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Wash contaminated clothing before reuse.

5. Fire-fighting measures

• •	
Suitable extinguishing media	Not available.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.

6. Accidental release measures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to
remove residual contamination. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not get in eyes, on skin, or on clothing. Avoid breathing gas. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Level 1 Aerosol.
inologing any moonpanolities	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	٦	Гуре			Value	
2-Butoxyethanol (CAS 111-76-2)	F	PEL			240 mg/m3	
,					50 ppm	
Propane (CAS 74-98-6)	F	PEL			1800 mg/m3	
					1000 ppm	
US. ACGIH Threshold L	imit Values					
Components	7	Гуре			Value	
2-Butoxyethanol (CAS 111-76-2)	٦	ΓWA			20 ppm	
Butane (CAS 106-97-8)	S	STEL			1000 ppm	
US. NIOSH: Pocket Guid	de to Chemical Haza	rds				
Components	٦	Гуре			Value	
2-Butoxyethanol (CAS 111-76-2)	1	ΓWA			24 mg/m3	
					5 ppm	
Butane (CAS 106-97-8)	7	ΓWA			1900 mg/m3	
					800 ppm	
Propane (CAS 74-98-6)	٦	ΓWA			1800 mg/m3	
					1000 ppm	
US. Workplace Environ	mental Exposure Le	vel (V	VEEL) Guides			
Components	7	Гуре			Value	
Diethylene Glycol Monoethyl Ether (CAS 111-90-0)	1	ΓWA			140 mg/m3	
,					25 ppm	
logical limit values						
ACGIH Biological Expo	sure Indices					
Components	Value		Determinant	Specimer	n Sampling Time	
2-Butoxyethanol (CAS 111-76-2)	200 mg/g		Butoxyacetic acid (BAA), with hydrolysis	Creatinine urine	in *	
* - For sampling details, p	lease see the source	docu				
oosure guidelines						
US - California OELs: S	kin designation					
2-Butoxyethanol (CA			Can be	absorbed th	rough the skin.	
US - Minnesota Haz Sub		appl				
2-Butoxyethanol (CA	-	• •		esignation ap	plies.	
	,			0		
duct name: 19 OZ SW PEN	TRATING COIL CLNR	I R 12	PK			S

US - Tennessee OELs: Skin	designation		
2-Butoxyethanol (CAS 111-76-2)		Can be absorbed through the skin.	
US NIOSH Pocket Guide to 0	Chemical Hazards: Skin desig	nation	
2-Butoxyethanol (CAS 111-76-2)		Can be absorbed through the skin.	
US. OSHA Table Z-1 Limits f	or Air Contaminants (29 CFR	1910.1000)	
2-Butoxyethanol (CAS 11	yethanol (CAS 111-76-2) Can be absorbed through the skin.		
Appropriate engineering controls	Provide eyewash station.		
Individual protection measures,	such as personal protective e	quipment	
Eye/face protection	Face shield is recommended. Wear safety glasses with side shields (or goggles).		
Skin protection			
Hand protection	For prolonged or repeated skir	n contact use suitable protective gloves.	
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.		
Respiratory protection	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.		
Thermal hazards	Wear appropriate thermal prot	ective clothing, when necessary.	
General hygiene considerations	after handling the material and	vays observe good personal hygiene measures, such as washing I before eating, drinking, and/or smoking. Routinely wash work nent to remove contaminants. Contaminated work clothing should not e.	

9. Physical and chemical properties

Appearance	
Physical state	Gas.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	212 °F (100 °C) estimated
Flash point	-156.0 °F (-104.4 °C) propellant estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.

Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Specific gravity	0.989 estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	No adverse effects due to inhalation are expected.
Skin contact	May cause an allergic skin reaction.
	2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

cute toxicity May cause a	n allergic skin reaction.
---------------------------	---------------------------

Acute toxicity	May cause an allergic skin reaction.	
Components	Species	Test Results
2-Butoxyethanol (CAS 111-76-2)		
<u>Acute</u>		
Dermal		
LD50	Guinea pig	7.3 ml/kg, 4 Days
		0.23 ml/kg, 24 Hours
	Rabbit	435 mg/kg, 24 Hours
		0.68 ml/kg, 24 Hours
		0.63 ml/kg
	Rat	> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rabbit	400 ppm, 7 Hours
	Rat	450 ppm, 4 Hours
Oral		
LD100	Rabbit	695 mg/kg
LD50	Dog	> 695 mg/kg
	Guinea pig	1414 mg/kg
	Mouse	1519 mg/kg
	Rat	1746 mg/kg

Components	Species	Test Results
Butane (CAS 106-97-8)		
Acute		
Inhalation	Maura	
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
Diethylene Glycol Monoethyl Ethe	r (CAS 111-90-0)	
<u>Acute</u>		
Dermal		
LD50	Guinea pig	5900 mg/kg, Days
	Rabbit	9143 mg/kg, 24 Hours
		8500 mg/kg, 2 Hours
Oral		
LD50	Guinea pig	4970 mg/kg
	Mouse	6031 mg/kg
	Rabbit	5600 mg/kg
	Rat	10502 mg/kg
		5.4 ml/kg
EDTA Tetrasodium Salt (CAS 64-	02-8)	J
<u>Acute</u>		
Oral		
LD50	Rat	1658 mg/kg
Propane (CAS 74-98-6)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h
Sodium Nitrite (CAS 7632-00-0)		
Acute		
Oral		
LD50	Rat	180 mg/kg
Terpene Hydrocarbons (CAS 689	56-56-9)	
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg, 24 Hours
Oral		
LD50	Rat	> 2000 mg/kg
	e based on additional component data not	
Skin corrosion/irritation	Prolonged skin contact may cause temp	orary irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory or skin sensitization	1	
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	May cause an allergic skin reaction.	
Germ cell mutagenicity	No data available to indicate product or a mutagenic or genotoxic.	any components present at greater than 0.1% are
Carcinogenicity	This product is not considered to be a ca	arcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall	Evaluation of Carcinogenicity
2-Butoxyethanol (CAS 11	,
OSHA Specifically Regulate	d Substances (29 CFR 1910.1001-1050)
Not regulated.	
US. National Toxicology Pro	ogram (NTP) Report on Carcinogens
Not listed.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	May be harmful if absorbed through skin.
	2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

12. Ecological information

cotoxicity	Harmful to	o aquatic life with long lasting effects.	
Components		Species	Test Results
2-Butoxyethanol (CAS	111-76-2)		
Aquatic			
Fish	LC50	Inland silverside (Menidia beryllina)	1250 mg/l, 96 hours
Diethylene Glycol Mono	bethyl Ether (CAS	111-90-0)	
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	> 10000 mg/l, 96 hours
EDTA Tetrasodium Sal	t (CAS 64-02-8)		
Aquatic			
Algae	IC50	Algae	1.01 mg/L, 72 Hours
Fish	LC50	Bluegill (Lepomis macrochirus)	472 - 500 mg/l, 96 hours
Sodium Nitrite (CAS 76	32-00-0)		
Aquatic			
Crustacea	EC50	Greasyback shrimp (Metapenaeus ensis)	16.14 - 26.61 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	0.15 - 0.25 mg/l, 96 hours

Bioaccumulative potential

Partition coefficient n-o	ctanol / water (log Kow)	
2-Butoxyethanol		0.83
Butane		2.89
Diethylene Glycol Monoe	thyl Ether	-0.54
Propane		2.36
Mobility in soil	No data available.	
Other adverse effects		nmental effects (e.g. ozone depletion, photochemical ozone creation uption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable, (each not exceeding 1 L capacity)
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
	LTD QTY
Packaging Exceptions	
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY
Transport in bulk according to	Not applicable.
Annex II of MARPOL 73/78 and	· · · TFF · · · · ·
the IBC Code	



15. Regulatory information

US federal regulations	This product is a "Hazardous Standard, 29 CFR 1910.1200		ed by the OSHA Hazard Communication
TSCA Section 12(b) Export I	Notification (40 CFR 707, Sub	pt. D)	
Not regulated.		• •	
CERCLA Hazardous Substa	nce List (40 CFR 302.4)		
Sodium Nitrite (CAS 7632	• •	Listed.	
SARA 304 Emergency release		2101001	
Not regulated.			
0	d Substances (29 CFR 1910.1	001-1050)	
Not regulated.			
Superfund Amendments and Re	authorization Act of 1986 (SA	RA)	
Hazard categories	Immediate Hazard - Yes	,	
	Delayed Hazard - No		
	Fire Hazard - Yes		
	Pressure Hazard - No		
	Reactivity Hazard - No		
SARA 302 Extremely hazard	ous substance		
Not listed.			
SARA 311/312 Hazardous	No		
chemical			
chemical SARA 313 (TRI reporting) Chemical name		CAS number	% by wt.
SARA 313 (TRI reporting) Chemical name			% by wt.
SARA 313 (TRI reporting)		111-76-2	1 - 2.5
SARA 313 (TRI reporting) Chemical name 2-Butoxyethanol Sodium Nitrite			<u> </u>
SARA 313 (TRI reporting) Chemical name 2-Butoxyethanol Sodium Nitrite Other federal regulations	112 Hazardous Air Pollutant	111-76-2 7632-00-0	1 - 2.5
SARA 313 (TRI reporting) Chemical name 2-Butoxyethanol Sodium Nitrite Other federal regulations Clean Air Act (CAA) Section	112 Hazardous Air Pollutant	111-76-2 7632-00-0	1 - 2.5
SARA 313 (TRI reporting) Chemical name 2-Butoxyethanol Sodium Nitrite Other federal regulations Clean Air Act (CAA) Section Not regulated.	112 Hazardous Air Pollutant 112(r) Accidental Release Pr	111-76-2 7632-00-0 s (HAPs) List	1 - 2.5 0.1 - 1
SARA 313 (TRI reporting) Chemical name 2-Butoxyethanol Sodium Nitrite Other federal regulations Clean Air Act (CAA) Section Not regulated.		111-76-2 7632-00-0 s (HAPs) List	1 - 2.5 0.1 - 1
SARA 313 (TRI reporting) Chemical name 2-Butoxyethanol Sodium Nitrite Other federal regulations Clean Air Act (CAA) Section Not regulated. Clean Air Act (CAA) Section Butane (CAS 106-97-8)		111-76-2 7632-00-0 s (HAPs) List	1 - 2.5 0.1 - 1
SARA 313 (TRI reporting) Chemical name 2-Butoxyethanol Sodium Nitrite Other federal regulations Clean Air Act (CAA) Section Not regulated. Clean Air Act (CAA) Section Butane (CAS 106-97-8) Propane (CAS 74-98-6) Safe Drinking Water Act	112(r) Accidental Release Pr	111-76-2 7632-00-0 s (HAPs) List	1 - 2.5 0.1 - 1
SARA 313 (TRI reporting) Chemical name 2-Butoxyethanol Sodium Nitrite Other federal regulations Clean Air Act (CAA) Section Not regulated. Clean Air Act (CAA) Section Butane (CAS 106-97-8) Propane (CAS 74-98-6) Safe Drinking Water Act (SDWA) US state regulations	112(r) Accidental Release Pr Not regulated.	111-76-2 7632-00-0 s (HAPs) List revention (40 CFR 6	1 - 2.5 0.1 - 1 68.130)
SARA 313 (TRI reporting) Chemical name 2-Butoxyethanol Sodium Nitrite Other federal regulations Clean Air Act (CAA) Section Not regulated. Clean Air Act (CAA) Section Butane (CAS 106-97-8) Propane (CAS 74-98-6) Safe Drinking Water Act (SDWA) US state regulations	112(r) Accidental Release Pr Not regulated.	111-76-2 7632-00-0 s (HAPs) List revention (40 CFR 6	1 - 2.5 0.1 - 1

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

2-Butoxyethanol (CAS 111-76-2) Butane (CAS 106-97-8)

US. Massachusetts RTK - Substance List

2-Butoxyethanol (CAS 111-76-2) Butane (CAS 106-97-8) Propane (CAS 74-98-6) Sodium Nitrite (CAS 7632-00-0)

US. New Jersey Worker and Community Right-to-Know Act

2-Butoxyethanol (CAS 111-76-2) Butane (CAS 106-97-8) Propane (CAS 74-98-6) Sodium Nitrite (CAS 7632-00-0)

US. Pennsylvania Worker and Community Right-to-Know Law

2-Butoxyethanol (CAS 111-76-2) Butane (CAS 106-97-8) Propane (CAS 74-98-6) Sodium Nitrite (CAS 7632-00-0)

US. Rhode Island RTK

Butane (CAS 106-97-8) Propane (CAS 74-98-6) Sodium Nitrite (CAS 7632-00-0)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

- Benzyl chloride (CAS 100-44-7) Listed: January 1, 1990
- US California Proposition 65 CRT: Listed date/Developmental toxin 2-Ethoxyethanol (CAS 110-80-5) Ethylene Glycol (CAS 107-21-1) Listed: June 19, 2015
- US California Proposition 65 CRT: Listed date/Male reproductive toxin

2-Ethoxyethanol (CAS 110-80-5) Listed: January 1, 1989

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	03-12-2018
Version #	01

	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision information	Product and Company Identification: Alternate Trade Names