

Version 1.0

Revision Date 02/21/2017

Print Date 10/04/2017

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

: ZEP STAINLESS STEEL POLISH AERO DZ Material name

Material number : 14301C

#### Manufacturer or supplier's details

Company	:	Zep Inc.
Address	:	11627 - 178 Street Edmonton, Alberta T5S 1N6 Canada
Telephone	:	404-352-1680

Telephone	:	404-35

Emergency telephone nu	mbe	rs
For SDS Information	:	Compliance Services 1-877-428-9937
For a Medical Emergency	:	877-541-2016 Toll Free - All Calls Recorded
For a Transportation	:	CHEMTREC: 800-424-9300 - All Calls Recorded.
Emergency		

#### Recommended use of the chemical and restrictions on use

: Cleaner Recommended use

### **SECTION 2. HAZARDS IDENTIFICATION**

#### **Emergency Overview**

Appearance	Aerosol containing a compressed gas
Colour	amber
Odour	characteristic

#### **GHS** Classification

Flammable aerosols Gases under pressure Skin irritation Eye irritation Skin sensitisation	<ul> <li>Category 1</li> <li>Compressed gas</li> <li>Category 2</li> <li>Category 2A</li> <li>Category 1</li> </ul>
GHS label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	<ul> <li>H222 Extremely flammable aerosol.</li> <li>H280 Contains gas under pressure; may explode if heated.</li> <li>H315 Causes skin irritation.</li> </ul>



Version 1.0	Revision Date 02/21/2017	Print Date 10/04/2017
	H317 May cause an allergic skin reacti H319 Causes serious eye irritation.	on.
Precautionary statements :	<ul> <li>Prevention:</li> <li>P210 Keep away from heat, hot surface and other ignition sources. No smoking P211 Do not spray on an open flame o P251 Do not pierce or burn, even after P261 Avoid breathing dust/ fume/ gas/ P264 Wash skin thoroughly after handli P272 Contaminated work clothing shout the workplace.</li> <li>P280 Wear protective gloves/ eye prote <b>Response:</b></li> <li>P302 + P352 IF ON SKIN: Wash with p P305 + P351 + P338 IF IN EYES: Rins for several minutes. Remove contact lee easy to do. Continue rinsing.</li> <li>P333 + P313 If skin irritation or rash oc advice/ attention.</li> <li>P362 + P364 Take off contaminated clar reuse.</li> <li>Storage:</li> <li>P410 + P412 Protect from sunlight. Do temperatures exceeding 50 °C/ 122 °F.</li> <li>Dispose of contents/container in accor regulation.</li> </ul>	<ul> <li>r other ignition source.</li> <li>use.</li> <li>mist/ vapours/ spray.</li> <li>ing.</li> <li>uld not be allowed out of</li> <li>ection/ face protection.</li> <li>olenty of water.</li> <li>e cautiously with water</li> <li>enses, if present and</li> <li>ccurs: Get medical</li> <li>Get medical advice/</li> <li>othing and wash it before</li> <li>not expose to</li> </ul>

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Hazardous components

Chemical name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 50 - < 70
Distillates (petroleum), hydrotreated light	64742-47-8	>= 10 - < 20
Solvent naphtha (petroleum), light aliph.	64742-89-8	>= 5 - < 10
(R)-p-mentha-1,8-diene	5989-27-5	>= 1 - < 5
carbon dioxide	124-38-9	>= 1 - < 5
Solvent naphtha (petroleum), heavy aliph.	64742-96-7	>= 1 - < 5
propan-2-ol	67-63-0	>= 1 - < 5
citral	5392-40-5	>= 0.1 - < 1

#### SECTION 4. FIRST AID MEASURES

General advice

: Move out of dangerous area.

Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.

## SAFETY DATA SHEET



# ZEP STAINLESS STEEL POLISH AERO DZ

Version 1.0	Revision Date 02/21/2017	Print Date 10/04/2017
If inhaled	: If unconscious place in recov advice. If symptoms persist, call a ph	
In case of skin contact	: If skin irritation persists, call Wash off immediately with pl minutes. If on clothes, remove clothes	lenty of water for at least 15
In case of eye contact	: Remove contact lenses. Protect unharmed eye. Keep eye wide open while rin If eye irritation persists, cons Rinse immediately with plent	
If swallowed	: Keep respiratory tract clear. Never give anything by mout If symptoms persist, call a ph DO NOT induce vomiting unl physician or poison control c	nysician. Iess directed to do so by a
Most important symptoms and effects, both acute and delayed		tion, redness, pain, and rash. posure (dose, concentration, eaction.
Notes to physician	: Treat symptomatically. Sym	ptoms may be delayed.

### SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Water spray jet	
Unsuitable extinguishing media	: High volume water jet	
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or wate courses.	÷r
Hazardous combustion products	: Carbon dioxide (CO2) Carbon monoxide Smoke	
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.	
Further information	<ul> <li>Collect contaminated fire extinguishing water separately. The must not be discharged into drains.</li> <li>Fire residues and contaminated fire extinguishing water mu be disposed of in accordance with local regulations.</li> </ul>	



Version 1.0	Revision Date 02/21/2017	Print Date 10/04/2017
	For safety reasons in case of fire, separately in closed containments. Use a water spray to cool fully clos	
Special protective equipment for firefighters	: Wear self-contained breathing app necessary.	aratus for firefighting if

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, : protective equipment and emergency procedures	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions :	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for : containment and cleaning up	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal.

### SECTION 7. HANDLING AND STORAGE

Advice on safe handling :	<ul> <li>Avoid exposure - obtain special instructions before use.</li> <li>Avoid contact with skin and eyes.</li> <li>For personal protection see section 8.</li> <li>Smoking, eating and drinking should be prohibited in the application area.</li> <li>Take precautionary measures against static discharges.</li> <li>Provide sufficient air exchange and/or exhaust in work rooms.</li> <li>Dispose of rinse water in accordance with local and national regulations.</li> <li>Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.</li> <li>Always replace cap after use.</li> <li>Do not breathe vapours or spray mist.</li> </ul>
Conditions for safe storage	<ul> <li>BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.</li> <li>No smoking.</li> <li>Containers which are opened must be carefully resealed and kept upright to prevent leakage.</li> <li>Observe label precautions.</li> <li>Keep in a dry, cool and well-ventilated place.</li> <li>Electrical installations / working materials must comply with</li> </ul>



Version 1.0

Revision Date 02/21/2017

Print Date 10/04/2017

the technological safety standards.

Materials to avoid

: Strong oxidizing agents

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type	Control	Basis
		(Form of	parameters /	
		exposure)	Permissible	
			concentration	
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	1 mg/m3	CA BC OEL
Distillates (petroleum),	64742-47-8	TWA	200 mg/m3	CA BC OEL
hydrotreated light				
		TWA	200 mg/m3	CA BC OEL
		TWA	200 mg/m3	CA AB OEL
carbon dioxide	124-38-9	TWA	5,000 ppm 9,000 mg/m3	CA AB OEL
		STEL	30,000 ppm	CA AB OEL
			54,000 mg/m3	
		TWA	5,000 ppm	CA BC OEL
		STEL	15,000 ppm	CA BC OEL
		STEV	30,000 ppm 54,000 mg/m3	CA QC OEL
		TWAEV	5,000 ppm	CA QC OEL
			9,000 mg/m3	
		TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m3	NIOSH REL
		ST	30,000 ppm	NIOSH REL
			54,000 mg/m3	
		TWA	5,000 ppm	OSHA Z-1
			9,000 mg/m3	
		TWA	10,000 ppm 18,000 mg/m3	OSHA P0
		STEL	30,000 ppm	OSHA P0
			54,000 mg/m3	
		PEL	5,000 ppm 9,000 mg/m3	CAL PEL
		STEL	30,000 ppm 54,000 mg/m3	CAL PEL
propan-2-ol	67-63-0	TWA	200 ppm 492 mg/m3	CA AB OEL
		STEL	400 ppm 984 mg/m3	CA AB OEL
	<u> </u>	TWA	200 ppm	CA BC OEL
	1	STEL	400 ppm	CA BC OEL
		TWAEV	400 ppm	CA QC OEL
			983 mg/m3	
		STEV	500 ppm 1,230 mg/m3	CA QC OEL
		TWA	200 ppm	ACGIH
	1			



 Version 1.0
 Revision Date 02/21/2017
 Print Date 10/04/2017

 STEL
 400 ppm
 ACGIH

 TWA
 400 ppm
 NIOSH REL

TWA	400 ppm 980 mg/m3	NIOSH REL
ST	500 ppm 1,225 mg/m3	NIOSH REL
TWA	400 ppm 980 mg/m3	OSHA Z-1
TWA	400 ppm 980 mg/m3	OSHA P0
STEL	500 ppm 1,225 mg/m3	OSHA P0
PEL	400 ppm 980 mg/m3	CAL PEL
STEL	500 ppm 1,225 mg/m3	CAL PEL
TWA (Inhalable fraction and vapor)	5 ppm	ACGIH

#### **Biological occupational exposure limits**

Component	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
PROPAN-2-OL	67-63-0	Acetone	Urine	End of	40 mg/l	ACGIH BEI
				shift at		
				end of		
				workwee		
				k		

### Engineering measures : effective ventilation in all processing areas

Personal protective equipment				
Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.		
Hand protection				
Material	:	Protective gloves		
Remarks	:	The suitability for a specific workplace should be discussed with the producers of the protective gloves.		
Eye protection	:	Ensure that eyewash stations and safety showers are close to the workstation location. Tightly fitting safety goggles		
		Eye wash bottle with pure water Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.		
Skin and body protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.		
Hygiene measures	:	When using do not eat or drink. When using do not smoke.		



Version 1.0

Revision Date 02/21/2017

Print Date 10/04/2017

Wash hands before breaks and at the end of workday.

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Aerosol containing a compressed ga	S
Colour	: amber	
Odour	: characteristic	
Odour Threshold	: No data available	
рН	: Not applicable	
Melting point/freezing point	: No data available	
Boiling point	: 82.22 °C	
Flash point	:	
	No data available	
Evaporation rate	: No data available	
Flammability (solid, gas)	: Extremely flammable aerosol.	
Upper explosion limit	: No data available	
Lower explosion limit	: No data available	
Vapour pressure	: No data available	
Relative vapour density	: No data available	
Density	: 0.856 g/cm3	
Solubility(ies)	. 0.000 g/omo	
Water solubility	: insoluble	
Solubility in other solvents	: not determined	
Partition coefficient: n- octanol/water	: No data available	
Auto-ignition temperature	: not determined	
Thermal decomposition	: No data available	
Viscosity		
Viscosity, kinematic	: No data available	
Heat of combustion	: 44.04 kJ/g	

#### SECTION 10. STABILITY AND REACTIVITY

Reactivity

- : Stable
- Chemical stability
- : Stable under normal conditions.



Version 1.0	Revision Date 02/21/2017	Print Date 10/04/2017
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.	
	Vapours may form explosive mixtur	e with air.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct	sunlight.
Incompatible materials	: Strong oxidizing agents	
Hazardous decomposition products	: Carbon oxides	

### SECTION 11. TOXICOLOGICAL INFORMATION

	Potential Health Effects		
	Aggravated Medical Condition	: None known.	
	Symptoms of Overexposure	: Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Effects are dependent on exposure (dose, concentration, contact time).	
	Carcinogenicity:		
	IARC	No component of this product present at levels greater than o equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.	r
Acu	te toxicity		
	Product:		
	Acute oral toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method	
	Acute dermal toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method	
	Components:		
	Distillates (petroleum), hydro Acute oral toxicity	<pre>btreated heavy naphthenic:</pre>	
	Acute inhalation toxicity	: LC50 Rat: > 5 mg/l Exposure time: 4 h	
	Acute dermal toxicity	: LD50 Rabbit: > 5,000 mg/kg	
	Distillates (petroleum), hydro Acute oral toxicity	otreated light: : LD50 Rat: > 5,000 mg/kg	
	Acute inhalation toxicity	: LC50 Rat: > 4.6 mg/l	



Version 1.0	Revision Date 02/21/2017	Print Date 10/04/2017
	Exposure time: 6 h	
Acute dermal toxicity	: LD50 Rat: > 2,000 mg/kg	
<b>(R)-p-mentha-1,8-diene:</b> Acute oral toxicity	: LD50 Oral Rat: 4,400 mg/kg	
Acute dermal toxicity	: LD50 Dermal Rabbit: > 5,000 mg/kg	9
<b>propan-2-ol:</b> Acute oral toxicity	: LD50 Oral Rat: 4,396 mg/kg Method: Calculation method	
Skin corrosion/irritation		
Product:		

Remarks: Irritating to skin.

#### Serious eye damage/eye irritation

#### Product:

Remarks: Irritating to eyes.

#### Respiratory or skin sensitisation

#### Product:

Remarks: Causes sensitisation.

#### Germ cell mutagenicity

No data available

#### Carcinogenicity

No data available

#### Reproductive toxicity

No data available

Distillates (petroleum), hydrotreated heavy naphthenic: Distillates (petroleum), hydrotreated light: Solvent naphtha (petroleum), light aliph.: (R)-p-mentha-1,8-diene: carbon dioxide: Solvent naphtha (petroleum), heavy aliph.: propan-2-ol: citral:

#### STOT - single exposure

No data available

#### STOT - repeated exposure

No data available

Aspiration toxicity

## SAFETY DATA SHEET



## ZEP STAINLESS STEEL POLISHAERO DZ

Version 1.0

Revision Date 02/21/2017

No data available

**Further information** 

#### Product:

Remarks: No data available

#### Components:

#### **Distillates (petroleum), hydrotreated light:** Remarks: No data available

#### SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

No data available

#### Persistence and degradability

No data available	
Bioaccumulative	potential

Product:	
Partition coefficient: n- octanol/water <u>Components:</u> citral :	: Remarks: No data available
Partition coefficient: n- octanol/water	: Pow: 2.76
Mobility in soil	
No data available	
Other adverse effects	
No data available <u>Product:</u>	
Additional ecological information	: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life.
<u>Components:</u> Dictillatos (potroloum) bydr	atracted light .
Distillates (petroleum), hydro	-

Additional ecological : No data available information

#### SECTION 13. DISPOSAL CONSIDERATIONS

#### **Disposal methods**

Waste from residues	:	The product should not be allowed to enter drains, water
		courses or the soil.



Version 1.0	Revision Date 02/21/2017	Print Date 10/04/2017
	Do not contaminate ponds, waterv chemical or used container. Dispose of in accordance with loc	
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch	n on, the empty drum.

#### SECTION 14. TRANSPORT INFORMATION

Transportation Regulation (TDG) / Règlement Pour Le Transport (TMD): (Canada): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IMDG (Vessel): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Cargo Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Passenger Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: 49 CFR (USA): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under Transport Dangerous Goods (TDG) Canada regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

#### SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

The components of this product are reported in the following inventories:

TSCAOn TSCA InventoryDSLAll components of this product are on the Canadian DSL

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

#### Inventory Acronym and Validity Area Legend:

**SECTION 16. OTHER INFORMATION** 



## ZEP STAINLESS STEEL POLISHAERO DZ

Version 1.0

Revision Date 02/21/2017

Print Date 10/04/2017

TSCA (USA), DSL (Canada), NDSL (Canada)

#### WHMIS - GHS Label Information: Hazard pictograms Signal word Danger: Hazard statements Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Precautionary statements Prevention: Keep aw ay from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash skin thoroughly after handling. Contaminated work clothing should not be allow ed out of the workplace. Wear protective gloves/eye protection/face protection. Response: IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash it before reuse. Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 Disposal: Dispose of contents/container in accordance with local regulation.

Version:	1.0
Revision Date:	02/21/2017
Print Date:	10/04/2017

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®,Zep Professional®, Enforcer®, National Chemical<sup>™</sup>, Selig<sup>™</sup>, Misty®, Next Dimension<sup>™</sup>, Petro®, i-Chem®, TimeMist®, TimeWick<sup>™</sup>, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National<sup>™</sup>, FC Forward Chemicals®,Rexodan®, Mykal<sup>™</sup>, and a number of private labeled brands.