

## ZEP WRITE AWAY AERO DZ

Version 1.0

Revision Date 02/28/2017

Print Date 09/28/2017

## SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP WRITE AWAY AERO DZ

Material number : 32401C

**Manufacturer or supplier's details**

Company : Zep Inc.

Address : 11627 - 178 Street  
Edmonton, Alberta T5S 1N6  
Canada

Telephone : 404-352-1680

**Emergency telephone numbers****For SDS Information** : Compliance Services 1-877-428-9937**For a Medical Emergency** : 877-541-2016 Toll Free - All Calls Recorded**For a Transportation  
Emergency** : CHEMTREC: 800-424-9300 - All Calls Recorded.**Recommended use of the chemical and restrictions on use**

Recommended use : Specialty Cleaner and Remover

## SECTION 2. HAZARDS IDENTIFICATION

**Emergency Overview**

Appearance	Aerosol containing a liquefied gas
Colour	colourless
Odour	characteristic

**GHS Classification**

Flammable aerosols : Category 1  
 Gases under pressure : Liquefied gas  
 Skin irritation : Category 2  
 Eye irritation : Category 2A  
 Skin sensitisation : Category 1

**GHS label elements**

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.  
 H280 Contains gas under pressure; may explode if heated.  
 H315 Causes skin irritation.

## ZEP WRITE AWAY AERO DZ

Version 1.0

Revision Date 02/28/2017

Print Date 09/28/2017

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

Precautionary statements

: **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/ eye protection/ face protection.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

**Storage:**

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:**

Dispose of contents/container in accordance with local regulation.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

## Hazardous components

Chemical name	CAS-No.	Concentration [%]
ethanol	64-17-5	>= 20 - < 30
benzyl alcohol	100-51-6	>= 20 - < 30
Citrus, ext.	94266-47-4	>= 10 - < 20
butane	106-97-8	>= 5 - < 10
propane	74-98-6	>= 1 - < 5

## SECTION 4. FIRST AID MEASURES

General advice

: Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.

If inhaled

: If unconscious place in recovery position and seek medical advice.  
If symptoms persist, call a physician.

**ZEP WRITE AWAY AERO DZ**

Version 1.0

Revision Date 02/28/2017

Print Date 09/28/2017

---

- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.  
Wash off immediately with plenty of water for at least 15 minutes.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
DO NOT induce vomiting unless directed to do so by a physician or poison control center.
- Most important symptoms and effects, both acute and delayed : Effects are immediate and delayed.  
Symptoms may include irritation, redness, pain, and rash.  
Causes skin irritation.  
Causes serious eye irritation.  
Review section 2 of SDS to see all potential hazards.
- Notes to physician : Treat symptomatically. Symptoms may be delayed.
- 

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon dioxide (CO<sub>2</sub>)  
Carbon monoxide  
Smoke
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.
-

**ZEP WRITE AWAY AERO DZ**

Version 1.0

Revision Date 02/28/2017

Print Date 09/28/2017

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Sweep up or vacuum up spillage and collect in suitable container for disposal.
- 

**SECTION 7. HANDLING AND STORAGE**

- Advice on safe handling : Do not breathe vapours or spray mist.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.  
Keep in a dry, cool and well-ventilated place.  
No smoking.
- Materials to avoid : Oxidizing agents
- 

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Components with workplace control parameters**

## ZEP WRITE AWAY AERO DZ

Version 1.0

Revision Date 02/28/2017

Print Date 09/28/2017

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ethanol	64-17-5	TWA	1,000 ppm 1,880 mg/m3	CA AB OEL
		STEL	1,000 ppm	CA BC OEL
		TWAEV	1,000 ppm 1,880 mg/m3	CA QC OEL
		TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,900 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,900 mg/m3	OSHA P0
		STEL	1,000 ppm	ACGIH
		PEL	1,000 ppm 1,900 mg/m3	CAL PEL
butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWA	600 ppm	CA BC OEL
		STEL	750 ppm	CA BC OEL
		TWAEV	800 ppm 1,900 mg/m3	CA QC OEL
propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWA	1,000 ppm	CA BC OEL
		TWAEV	1,000 ppm 1,800 mg/m3	CA QC OEL
		TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
TWA	1,000 ppm 1,800 mg/m3	OSHA P0		
PEL	1,000 ppm 1,800 mg/m3	CAL PEL		

**Engineering measures** : effective ventilation in all processing areas

**Personal protective equipment**

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves  
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection

: Impervious clothing

**ZEP WRITE AWAY AERO DZ**

Version 1.0

Revision Date 02/28/2017

Print Date 09/28/2017

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Aerosol containing a liquefied gas

Colour : colourless

Odour : characteristic

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : Not applicable

Boiling point : 79.44 °C

Flash point :  
No data available

Evaporation rate : not determined

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : Not applicable

Relative vapour density : No data available

Density : 0.844 g/cm<sup>3</sup>

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : Not applicable

Heat of combustion : 39.23 kJ/g

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

## ZEP WRITE AWAY AERO DZ

Version 1.0

Revision Date 02/28/2017

Print Date 09/28/2017

Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: Carbon oxides

## SECTION 11. TOXICOLOGICAL INFORMATION

**Potential Health Effects**

Aggravated Medical Condition : None known.

Symptoms of Overexposure : Effects are immediate and delayed.  
Symptoms may include irritation, redness, pain, and rash.

**Carcinogenicity:****IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**ACGIH**

Confirmed animal carcinogen with unknown relevance to humans

ethanol

64-17-5

**Acute toxicity****Product:**

Acute oral toxicity : Acute toxicity estimate : 2,021 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 6.06 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

**Components:****ethanol:**

Acute oral toxicity : LD50 Oral Rat: 7,060 mg/kg

**ZEP WRITE AWAY AERO DZ**

Version 1.0

Revision Date 02/28/2017

Print Date 09/28/2017

Acute inhalation toxicity : LC50 Rat: 124.7 mg/l  
Exposure time: 4 h

**benzyl alcohol:**  
Acute dermal toxicity : LD50 Rabbit: 1,250 mg/kg

**butane:**  
Acute inhalation toxicity : LC50 Mouse: 1,237 mg/l  
Exposure time: 2 h

LC50 Rat: 1,355 mg/l

**propane:**  
Acute inhalation toxicity : LC50 Mouse: 1,237 mg/l  
Exposure time: 2 h

LC50 Rat: 658 mg/l  
Exposure time: 4 h

LC50 Rat: 1,355 mg/l

**Skin corrosion/irritation**

**Product:**

Remarks: Irritating to skin.

**Serious eye damage/eye irritation**

**Product:**

Remarks: Severe eye irritation

**Respiratory or skin sensitisation**

**Product:**

Remarks: Causes sensitisation.

**Germ cell mutagenicity**

No data available

**Carcinogenicity**

No data available

**Reproductive toxicity**

No data available

- ethanol:**
- benzyl alcohol:**
- Citrus, ext.:**
- butane:**
- propane:**

**STOT - single exposure**



**ZEP WRITE AWAY AERO DZ**

Version 1.0

Revision Date 02/28/2017

Print Date 09/28/2017

---

No data available

**STOT - repeated exposure**

No data available

**Aspiration toxicity**

No data available

**Further information****Product:**Remarks: No data available

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential****Product:**

Partition coefficient: n-octanol/water : Remarks: No data available

**Components:****benzyl alcohol :**  
Partition coefficient: n-octanol/water : Pow: 0.87**butane :**  
Partition coefficient: n-octanol/water : Pow: 2.89**Mobility in soil**

No data available

**Other adverse effects**

No data available

**Product:**Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life.

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**Waste from residues : The product should not be allowed to enter drains, water courses or the soil.

---

**ZEP WRITE AWAY AERO DZ**

Version 1.0

Revision Date 02/28/2017

Print Date 09/28/2017

Do not contaminate ponds, waterways or ditches with chemical or used container.  
Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

**SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation (TDG) / Règlement Pour Le Transport (TMD): (Canada):  
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IMDG (Vessel):  
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Cargo Air):  
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Passenger Air):  
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: 49 CFR (USA):  
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under Transport Dangerous Goods (TDG) Canada regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

---

**SECTION 15. REGULATORY INFORMATION**

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

**The components of this product are reported in the following inventories:**

**TSCA** On TSCA Inventory  
**DSL** All components of this product are on the Canadian DSL

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

**Inventory Acronym and Validity Area Legend:**

## ZEP WRITE AWAY AERO DZ

Version 1.0

Revision Date 02/28/2017

Print Date 09/28/2017

TSCA (USA), DSL (Canada), NDSL (Canada)

## SECTION 16. OTHER INFORMATION

## WHMIS - GHS Label Information:

Hazard pictograms



Signal word

: **Danger:**

Hazard statements

: Extremely flammable aerosol. Contains gas under pressure; may explode if heated.  
Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

Precautionary statements

:

**Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/ eye protection/ face protection.

**Response:** IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash it before reuse.

**Storage:** Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:** Dispose of contents/container in accordance with local regulation.

Version:	1.0
Revision Date:	02/28/2017
Print Date:	09/28/2017

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes.

This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.